

# M12 Circular Connector




## M12 Male Straight 8 Pin Connector

### Product Image



Product may differ from image.

### Product Diagram



All dimensions are in mm.

### General Specification

Rated Operational Voltage	30 V
Current Rating	2A
Insulation Resistance	>= 100 MΩ
Temperature Range	-25°C ... +75°C
Tightening Torque	0.6 Nm
Degree of Protection	IP67
Coding	A-Coded


### Material Specification

Grip Material	PU
Contact	Cu-Zn
Contact Plating	Gold Flash
Contact Carrier	Nylon 66
Grip Colour	Black
Coupling Nut	Brass Nickel-Plated

### Cable Specification

Cable Length-L	2 m
Cable Type	8 Core PUR Multi Strand
Sheath Colour	Black
Cross Section of Wire	0.25 sq. mm
Core Dia	1.35 mm
Cable Dia	6.3 ± 0.1 mm
Termination	Partially Stripped

### Pin Assignment



### Specification & Approval

RoHS	Compliant with Exemption
RoHS exemption	6©: Copper alloy containing up to 4 % lead by weight
REACH SVHC substances	Yes
REACH SVHC substances	CAS 7439-92-1 (Lead)
CE	Yes
Standard	IEC 61076-2-101

### Ordering Part No.

Cable Length	Part Number
2 m	CBM12-S88N0-02BPUR
3 m	CBM12-S88N0-03BPUR
5 m	CBM12-S88N0-05BPUR
10 m	CBM12-S88N0-10BPUR
15 m	CBM12-S88N0-15BPUR

\*Please contact factory for customized cable lengths.