


Product Image



Product Diagram



General Specification

Rated Operational Voltage	60 V
Current Rating	1.5A
Insulation Resistance	>= 100 MΩ
Temperature Range	-25°C ... +75°C
Degree of Protection	M12:IP67 / RJ45:IP20
Coding	D-coded
Mounting	Rear


Material Specification

M12		RJ45
Housing Material	Brass Ni Plated	PBT
Contact	Cu-Zn	Phosphor Bronze
Contact Plating	Gold Flash	Gold Flash
Contact Carrier	Nylon 66	PBT
O-Ring	Neoprene	
Grip Colour		Black
Pole	4	
Clamp Nut	M16 x 1.5	

Cable Specification

Cable Length-L	0.3 m
Cable Type	Cat5e PVC (2 x 2 Twisted Pair)
Sheath Colour	Green
Cross Section of Wire	AWG 22
Cable Dia	6.5 ± 0.2 mm
Core Insulation	PE
Termination	RJ45
Transfer Parameters	CAT5E
Transfer Rate	up to 100 Mbit/s
Shield Braiding	75%

Pin Assignment



Wiring Diagram

M12	Colour	RJ45
1	Yellow	1
2	White	3
3	Orange	2
4	Blue	6
Shield		

Specification & Approval

RoHS	Compliant with Exemption
RoHS exemption	6©: Copper alloy containing up to 4 % lead by weight
REACH SVHC substances	Yes
REACH SVHC substances	CAS 7439-92-1 (Lead)
CE	Yes
Standard	IEC 61076-2-101

Ordering Part No.

Cable Length	Part Number
0.3 m	CDM12RMBR4D-MRJ45-0.3GVC5-SH
0.5 m	CDM12RMBR4D-MRJ45-0.5GVC5-SH
01 m	CDM12RMBR4D-MRJ45-01GVC5-SH
02 m	CDM12RMBR4D-MRJ45-02GVC5-SH

***Please contact factory for customized cable lengths.**